

DiluFlow Elite 1kg

Gravimetric dilutor (1 kg)

Ref. 503 101 (1 kg single pump) - **Ref. 503 201** (1 kg double pump)



Standards:



Traceability:



Manufactured under:



DiluFlow Elite 1kg automatically dilutes a solid sample in seconds, with the appropriate weight of diluent. Available in single or double pump. Ideal for the cosmetics and pharmaceutical industries and veterinary.

OVERVIEW

- 304L stainless steel body
- BagOpen height < 30 cm
- Removable DripTray (patented)
- BagOpen with GeckoGrip system (patented)
- Magnetic stand for BagOpen (patented shape)
- LightCode: color status LED
- Compatible with Booster Kit
- Stainless casting electromechanical core
- Robotic arm
- Protection for dispensing nozzle
- Up to 6 pumps
- Multi-dispensing mode (patented)
- Powder mode
- Weighing mode
- Auto-tare function
- 24 editable programs
- Bi-directional connectivity
- 1 g dilution to 1/10th

SPECIFICATIONS

- Resolution up to 200 g: 0.01 g
- Weighing range: 0.1 to 1000 g
- Max weight without support: 1500 g
- Weighing accuracy: 0 to 20 g: ± 0.01 g / 20 to 1000 g: ± 0.05 %
- Dilution factor: 1/2 to 1/1000, customizable fractions
- Minimum weight required for dilution: 0.5 g (with a recommended dilution factor of 10)
- Minimum weight required for distribution: 5 g
- Dilution/distribution accuracy: > 99% in Standard or Accurate mode (in optimal conditions)
- Dilution time for a 25 g sample diluted at 1/10: < 8 s (with Booster Kit in Fast mode)
- Dispensing time for 90 mL: < 6 s (with Booster Kit in Fast mode)
- Dispensing time for 225 mL: < 9 s (with Booster Kit in Fast mode)
- Max number of pumps: 2 integrated + 4 externals
- Dispensing/distribution mode: Fast - Standard - Accurate

1 / 4

FT_003734_Technical File DiluFlow Elite 1 kg_EN_02_01 Pictures and information are not contractually binding. This document is the translation of the French brochure. Adjustable distribution system (Ref. 505 005) and tongs platform (Ref. 505 003) on the picture are sold separately. DiluFlow is trademark. INTERSCIENCE reserves the right to change or improve the specifications of its products without notice. Please visit www.interscience.com for current updates and additional information. RCS 950 356 220 Versailles. INTERSCIENCE SARL F78860

interscience in the world

PARIS

Phone: +33 1 34 62 62 61
info@interscience.com

FRANKFURT

Phone: +49 611 7238 7770
sales.germany@interscience.com

BOSTON

Phone: +1 781 937 0007
sales.usa@intersciencelab.com

SHANGHAI

电话: +86 178 2123 6642
sales.china@interscience.cn

SINGAPORE

Phone: +65 6977 7232
sales.asia@interscience.com

TOKYO

Phone: +81 3 6712 9715
sales.japan@interscience.com

- Language: English, French
 - Voltage - frequencies: 100-240V~ 50-60Hz
 - Fuses: T3,15A L 250V 5x20 mm
 - Power max: 60 W
 - International protection marking: IP32
 - Warranty: 1 year
 - Availability of spare parts: 10 years
-
- In compliance with standards ISO 7218, ISO 6887
 - Manufactured under CE, RoHS 2002/95/EC, WEEE 2002/95/EC
 - Designed and made in France

TRACEABILITY

- Traceability: Printer / Export to Excel™ / CSV file export on USB stick / Bi-directional connection to LIMS
- Type of LIMS connection: File sharing, web service
- Exported data: Sample weight / Total weight / Dilution factor / Dilution accuracy / Diluent / Sample number / Diluent lot number / Date / Time / Last calibration date / Name of operator / Name of program
- Connection: 2 USB ports (type A) to connect a printer, keyboard, bar-code reader, USB stick / 1 USB port (type B) to connect a computer / Jack socket to connect a foot pedal / Handy gun / Ethernet connection for LIMS

DiluFlow Elite 1 kg single pump

Ref: 503 101

- Dimensions (w x d x h): 31.3 x 42.1 x 37.7 cm, gross weight: 13.00 kg
- Box (w x d x h): 55 x 55 x 53 cm, net weight: 18.90 kg

DiluFlow Elite 1 kg double pump

Ref: 503 201

- Dimensions (w x d x h): 37 x 42.1 x 37.7 cm, gross weight: 15.30 kg
- Box (w x d x h): 55 x 55 x 53 cm, net weight: 22.00 kg

DELIVERED WITH

- 1 drip tray 400
- 1 or 2 pumps
- 1 protection for dispensing nozzles
- 1 dispensing assembly (GL45 - Ø 3,2 mm) per pump
- 1 USB stick
- 1 USB cable
- 1 USB A Male / A Female extension cable
- 1 power cord
- 1 **BagOpen** 400 for dilutors (stainless steel)
- 1 user's manual
- 10 GeckoGrip
- 1 set of adhesive gum
- 1 Allen wrench
- Blender bags samples
- 1 conformity certificate / warranty card

ACCESSORIES

- **Ref. 410 130** Film for printer: Thermal transfer film for printer
- **Ref. 410 150** Printer: Thermal printer (RS 232 and USB output).
Delivered with 1 thermal transfer film + power cable + USB cable

2 / 4

FT_003734_Technical File DiluFlow Elite 1 kg_EN_02_01 Pictures and information are not contractually binding. This document is the translation of the French brochure. Adjustable distribution system (Ref. 505 005) and tongs platform (Ref. 505 003) on the picture are sold separately. DiluFlow is trademark. INTERSCIENCE reserves the right to change or improve the specifications of its products without notice. Please visit www.interscience.com for current updates and additional information. RCS 950 356 220 Versailles. INTERSCIENCE SARL F78860

interscience in the world

PARIS

Phone: +33 1 34 62 62 61
info@interscience.com

FRANKFURT

Phone: +49 611 7238 7770
sales.germany@interscience.com

BOSTON

Phone: +1 781 937 0007
sales.usa@intersciencelab.com

SHANGHAI

电话: +86 178 2123 6642
sales.china@interscience.cn

SINGAPORE

Phone: +65 6977 7232
sales.asia@interscience.com

TOKYO

Phone: +81 3 6712 9715
sales.japan@interscience.com

- Ref. 413 002 **2L bottle (GL45):** Set of 3 GL45 glass bottle (2L), autoclavable
- Ref. 505 001 **BagOpen 400 for dilutors:** Stand for 400 mL bags
- Ref. 505 002 **Weighing platform:** To weigh and support a container. Not delivered with container.
- Ref. 505 003 **Tongs platform:** To hold a tube (ø 10 to 60 mm). Not delivered with tube.
- Ref. 505 005 **Adjustable distribution system:** Ideal to fill various containers.
Delivered with a nozzle holder + screws + adjustable nozzle (Ø 3.2 mm - L: 23.5 cm) + adjustable nozzle (Ø 6.4 mm - L: 12 cm) + Allen key
- Ref. 505 007 **Pump module:** External module with single pump
+ 513 043: Dispensing assembly (GL45 - Ø 6.4 mm)
- Ref. 505 008 **6 nozzles holder:** Can hold up to 6 nozzles
- Ref. 505 009 **GeckoGrip for BagOpen 400/3500:** Set of 10 adhesives to hold the bag in place
Compatible with BagOpen 400 and 3500
- Ref. 505 010 **Integrable stand for broth bags:** Integrated to the unit, to hold one broth bag.
Delivered with 4 screws + Torx screwdriver.
- Ref. 505 014 **BagOpen 80/100 mL for dilutors:** Stand for 80/100 mL bags.
- Ref. 505 015 **GeckoGrip for BagOpen 80/100:** Set of 10 adhesives for DiluFlow BagOpen 80/100
- Ref. 505 016 **BagOpen 400 for dilutors (stainless steel):** Stainless steel stand for 400 mL bags
- Ref. 507 008 **Foot pedal:** For hands-free dispensing. Connection with a 3.5 mm Jack
- Ref. 511 000 **Booster kit:** Booster pump + 2 silicone tubings for pump part (20 cm each), inner ø 6.4 mm + 2 "Y"
- Ref. 513 001 **5L bottle (GL45):** GL45 glass bottle (5L), autoclavable
- Ref. 513 005 **Certified standard weight (500 g):** 500 g COFRAC calibrated weight, type F1
- Ref. 513 015 **Independent stand for broth bags:** Independent stand for 2 broth bags
- Ref. 513 053 **Support for distribution set with 0.2 µm filter:** 1 holder for dispensing assembly with 0.2 µm filter + 1 knurled head screw - Compatible with Steriwat filtration system
- Ref. 521 012 **Sticker for printer:** Set of 2 rolls of 1000 stickers for thermal printer
Label size: 70 x 45 mm
- Ref. 521 110 **Paper for printer:** Set of 2 thermal paper rolls for printer
- Ref. 522 000 **Bar-code reader:** Bar-code reader (1D/2D)
- Ref. 561 001 **Handy Gun:** Dispensing control with handy gun including electronic start button

TUBINGS

- Ref. 505 012 **Adjustable nozzles (L 23.5 cm - tubings Ø 3.2 mm):** Set of 5 adjustable PEEK nozzles (Length: 23.5 cm - For inner Ø 3.2 mm tubings)
- Ref. 513 008 **Booster kit dispensing assembly (GL45 - Ø 3.2 mm):** Set of silicone tubings inner ø 3.2 mm + GL45 screw cap + tube weight + nozzle + cap + filter "Y"
- Ref. 513 009 **Tubings + Y (Ø 3.2 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner ø 3.2 mm
- Ref. 513 020 **Trocar:** Stainless steel trocar + cap for broth bags
- Ref. 513 023 **PTFE filters 0.2 µm (Ø 25 mm):** Set of 5 autoclavable filters (0.2 µm) for GL45 bottle
- Ref. 513 024 **Nozzles (tubings Ø 4,8 - 8 mm):** Set of 5 PEEK nozzles + caps for tubings from 4.8 to 8 mm inner diameter
- Ref. 513 039 **Tube weights (ø 6 mm):** Set of 5 PTFE tube weights - ø 6 mm
- Ref. 513 040 **Nozzles (tubings Ø 1.6 - 3.2 mm):** Set of 5 PEEK nozzles + caps for tubings from 1.6 to 3.2 mm inner diameter
- Ref. 513 041 **Booster kit dispensing assembly (GL45 - Ø 6.4 mm):** Set of silicone tubings inner ø 6.4 mm + GL45 screw cap + tube weight + nozzle + cap + filter + "Y"
- Ref. 513 042 **Tubings + Y (Ø 6.4 mm) :** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner ø 6.4 mm
- Ref. 513 043 **Dispensing assembly (GL45 - Ø 6.4 mm):** Set of silicone tubings inner ø 6.4 mm + GL45 screw cap + tube weight + nozzle + cap + filter
- Ref. 513 044 **Tubings (Ø 6.4 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + straight connectors) - inner ø 6.4 mm
- Ref. 513 045 **Dispensing assembly (GL45 - Ø 3,2 mm):** Set of silicone tubings inner ø 3.2 mm + GL45 screw cap + tube weight + nozzle + cap + filter
- Ref. 513 047 **Tubings (Ø 3.2 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + straight

- connectors) - inner ø 3.2 mm
- Ref. 513 048 **Nozzle cap (Ø 1.6 - 3.2 mm):** Set of 5 protections for nozzles (tubings Ø 1.6 - 3.2 mm) or trocar
- Ref. 513 049 **Nozzle cap (Ø 4.8 - 8 mm):** Set of 5 protections for nozzles (tubings Ø 4.8 - 8 mm)
- Ref. 513 050 **Dispensing assembly with 0.2 µm filter (GL45 - Ø 6.4 mm):** Set of silicone tubings inner Ø 6.4 mm + GL45 screw cap + filter + tube weight + nozzle + cap + 0.2 µm filter
- Ref. 513 051 **Dispensing assembly + Y with 0.2 µm filter (GL45 - Ø 6.4 mm):** Set of silicone tubings inner Ø 6.4 mm + GL45 screw cap + filter + tube weight + nozzle + cap + "Y" + 2 filters 0.2 µm
- Ref. 513 052 **Tubings for pump with filter 0.2 µm (Ø 6.4 mm):** Set of 2 Tygon™ tubing for pump part (50 cm) + 2 filters 0.2 µm. inner Ø 6.4 mm
- Ref. 561 302 **Tubings for pump (Ø 3.2 mm):** Set of 6 Tygon™ tubings for pump part (20 cm).inner ø 3.2 mm
- Ref. 561 304 **Tubings for pump (Ø 6.4 mm):** Set of 6 Tygon™ tubings for pump part (20 cm).inner ø 6.4 mm
- Ref. 561 401 **Autoclavable GL45 stopper + 0.2 µm filter:** Autoclavable GL45 stopper + 0.2 µm filter
- Ref. 561 403 **Straight connectors (tubings ø 6.4 - 8 mm):** Set of 6 straight plastic connectors for 6.4 et 8 mm tubings
- Ref. 561 404 **Straight connectors (tubings ø 3.2 - 4.8 mm):** Set of 6 straight plastic connectors for 4.8 et 3.2 mm tubings
- Ref. 562 401 **Y connectors (tubings ø 6.4 - 8 mm):** Set of 6 "Y" plastic connectors for 6.4 and 8 mm tubings
- Ref. 562 402 **Y connectors (tubings ø 3.2 mm):** Set of 6 "Y" plastic connectors for 3.2 mm tubings