


Scan 1200

HD automatic colony counter

Inhibition zone reader

Ref. 437 000



Standards:



Integrated database:



Traceability and high technology:



Manufacture:



Scan 1200 is an HD automatic colony counter. It adapts itself to all media and counts in 1 click all colonies even the smallest ones. It ensures accuracy and excellent reproducibility. Images and results are saved automatically. Scan 1200 is also an inhibition zone reader.

OVERVIEW

- Painted stainless steel shell
- LIMS/SIL connection
- USB connection
- Available with dataLink / dataLink pro traceability system
- Counting on pour, surface, Spiral and circular plated Petri dishes
- Counting on chromogenic dishes
- Counting on Petrifilm™, Compact Dry™, MC-Media Pad™, EasyPlate™, filtration membranes
- Automatic counting
- Inhibition zone reading

COUNTING

- Counting: automatic with manual control (add or remove colonies)
- Automatic separation of clustered colonies
- Creation of polygonal exclusion zones
- Counting time: up to 1000 colonies per second
- Minimal size of colony: 0.05 mm

INHIBITION ZONE READING

- Antibiotic disc detection: Automatic with possibility to manually add or remove
- Automatic detection of antibiogram support: Disks (several brands simultaneously), wells
- Display resolution: ± 0.1 mm
- Accuracy of antibiogram measurement: ± 0.3 mm
- Number of antibiotic paper disks: Up to 7 antibiotics on a $\varnothing 90$ mm Petri dish
- Reading time: 7 inhibition zone reading between 1 to 3 s
- Interpretation system: CA-SFM Human Health / EUCAST / CA-SFM Veterinary / CLSI (Clinical, Laboratory Standards Institute) / Customizable list

SPECIFICATIONS

- HD CCD color camera

1 / 3

FT_003773_Scan 1200_EN_01_02 Pictures and information are not contractually binding. Scan is trademark. INTERSCIENCE reserves the right to change or improve the specifications of its products without notice. Please visit www.interscience.com for current updates and additional information. RCS 950 356 220 Versailles. INTERSCIENCE SARL F78860

interscience in the world

PARIS

Phone: +33 1 34 62 62 61
info@interscience.com

FRANKFURT

Phone: +49 611 7238 7770
sales.germany@interscience.com

BOSTON

Phone: +1 781 937 0007
sales.usa@intersciencelab.com

SHANGHAI

电话: +86 178 2123 6642
sales.china@interscience.cn

SINGAPORE

Phone: +65 6977 7232
sales.asia@interscience.com

TOKYO

Phone: +81 3 6712 9715
sales.japan@interscience.com

- HD Japanese lens
- Zoom x 28
- Resolution (megapixels): 1.2
- White LED lighting technology: Dark Field
- LED lighting system: Automatic with 6 combinations, top and/or bottom light, white or black background
- Petri dish sizes: Ø 55 mm - Ø 90 mm
- Color detection: 4 colors on the same dish + 2 colors to exclude
- Supply voltage and frequency: 100-240 V~ 50-60 Hz
- Fuses: T3.15 A L 250 V 5x20 mm
- Max. power: 20 W
- International protection marking: IP00
- Warranty: 3 years (after recording the warranty card)
- Spare parts availability: 10 years
- In compliance with 21 CFR part 11, ISO 7218 and AOAC 977.27

SOFTWARE

- Languages: English, French, Japanese, Chinese, Russian, Spanish, German
- License type: Perpetual
- Software updates: 3 years excluding qualification (after recording the warranty)

TRACEABILITY

- USB Data export: Recountable session, Excel™, PDF report, jpg, png and bmp images
- Data security: Modified data traceability in conformity with 21CFR Part 11
- Results/traceability: Image / sample number / comments / date / time / antibiotic name / bacterial name / measured diameter / result categorized according to standards / minimum and maximum critical diameter

PC MINIMUM REQUIREMENTS

- Operating system: Windows™ 10 or 11 (or higher)
- Processor: Intel i5, 13th or 14th generation minimum
- RAM: 4 GB for use of the Scan
- Features: USB port free
- Screen: 1280 X 1024 pixels or higher

WEIGHTS & DIMENSIONS

Dimensions (w x d x h):	28.8 x 26.3 x 37.3 cm
Net weight:	9.40 kg
Gross weight:	13.10 kg
Box (w x d x h):	57 x 42 x 42 cm

DELIVERED WITH

- 1 Scan software
- 1 15V power supply
- 1 power supply
- 1 USB cable
- 3 validation plates
- 1 user manual
- 1 conformity certificate / warranty card

MANUFACTURING

- CE, UKCA, ROHS, WEEE certification
- Designed and made in France
- GLP-compliant use (Good Laboratory Practice)

OPTIONS / ACCESSORIES

- Ref. 435 702 **Optical cleaner + wipes:** Optical cleaner and 50 wipes
- Ref 436 005 **Adapter for Petri dish (55 mm):** Adapter for Ø 55 mm-dishes for Scan 300 / 500/ 1200
- Ref 437 001 **Adapter for MC-Media Pad™:** Adapter for MC-Media Pad™ for Scan 1200
- Ref 437 002 **Adapter for PetriFilm™:** Adapter for Petrifilm™ for Scan 1200
- Ref 437 003 **Adapter for Easy Plate™:** Adapter for Easy Plate™ for Scan 1200
- Ref 437 004 **Adapter for Compact Dry™:** Adapter for Compact Dry™ for Scan 1200
- Ref. 437 006 **Validation plates for counter and reader:**
Set of 3 validation plates (diameter, colony and antibiogram) - Compatible with Scan 500, 1200, 3000 Ai and 5000 Ai
- Ref. 437 007 **Certified validation plates for counter and reader:**
Set of 3 validation plates (diameter, colony and antibiogram) with certificate - Compatible with Scan 500, 1200, 3000 Ai and 5000 Ai
- Ref. 522 000 **Barcode reader:** Barcode reader (1D / 2D)