

## FlexiPump® Scale

Peristaltic pump for liquid distribution


Ref. 563 000



Certification:



Traceability :



Manufacture :



**FlexiPump® Scale** is a liquid dispenser that combines the power of a peristaltic pump with the precision of an integrated weighing platform. **FlexiPump® Scale** pushes the boundaries to meet the most demanding laboratory requirements. **FlexiPump® Scale** is a complete, agile solution for a wide range of distributions.

### OVERVIEW

- All stainless steel 304 L body
- Higher control with handy gun
- Traceability (computer, printer, USB key)
- High-precision, high-flow double-head pump
- Integrated weighing platform
- Autocalibration with customizable frequency (Patented)
- Compatible with Jumbo pack for large volume distribution

### DISTRIBUTION

- Volume dispensed in Dose or Multidose mode: 50 µL to 99 L
- Dispensing volume in Dose on scale: 1 mL to 6.5 L
- Weighing range: 0.1 to 6500 g
- Weighing resolution up to 200 g: 0.01 g
- Weighing accuracy:
  - 0 to 100 g = ± 0.05 g
  - 100 to 6500 g = 0.1%
- Typical accuracy with tubings inner Ø 3.2 mm
  - 9 mL : ± 0.9%
  - 18 mL : ± 0.5%
  - 225 mL : ± 0.4%
- Precision range in scale dispensing mode :
  - 0 to 1% in Accurate mode
  - 0 to 2% in Fast or Normal mode (measured for each distribution)
- Distribution modes:
  - Continuous
  - Doses with or without autocalibration
  - Multidose with or without autocalibration
  - Dose on scale
- 32 customizable programs
- Pause time in Multidose mode: adjustable from 0.1 to 99.9 s
- Number of distributions for 9 mL tubes: 40 x 9 mL tubes in 1 min (in Multidose mode with 0.1 s delay in optimal conditions)
- Number of distributions for 18 mL plates: 29 plates of 18 mL in 1 min (in Multidose mode with 0.1 s delay in optimal conditions)

- Number of distributions for 220 mL sample bags: 8 distributions of 220 mL in 1 min (in Multidose mode with 0.1 s delay in optimal conditions)
- Watson Marlow™ slow-pulse double pump with 6 rollers
- Flow rate: 6 mL/min to 5 L/min
- Speed: 10 to 550 rpm
- Tubings materials: Tygon™ (for pump head) and silicone

## SPECIFICATIONS

- Connections: 2 x USB type A, USB type B, 3.5 mm jack, socket for weighing platform
- Supply voltage and frequency: 100-240 V ~ 50-60 Hz
- Fuses: T 2.5 A L 250 V 5x20 mm
- IP: 31
- Warranty: 1 year
- Spare parts availability: 10 years
- Designed and manufactured in France
- In compliance with ISO 7218, ISO 6887 and FDA BAM (Bacteriological Analytical Manual) standards
- CE, UKCA, RoHS, WEEE certification
- Suitable for use in accordance with Good Laboratory Practice (GLP)

## TRACEABILITY

- Links: USB type A (printer, USB stick), USB type B (computer)
- Data type: Operator name, distribution mode accuracy, last calibration, date, time, speed, inner tube diameter, target weight, measured weight
- Data export: CSV file compatible with Excel™, Open Office Calc™, LIMS

## WEIGHTS AND DIMENSIONS

FlexiPump® Scale + Weighing platform: Ø 17 x 5.4 cm	<ul style="list-style-type: none"> <li>• Dimensions (W x D x H) : 16.1 x 33.2 x 20.8 cm</li> <li>• Net weight : 7.5 kg</li> <li>• Gross weight : 11.26 kg</li> </ul>
FlexiPump® Scale + Weighing platform: Ø 17 x 5.4 cm + Dispensing gun (ref. 561 001)	<ul style="list-style-type: none"> <li>• Dimensions (W x D x H) : 19.4 x 33.5 x 20.8 cm</li> <li>• Net weight : 7.65 kg</li> <li>• Gross weight : 11.41 kg</li> </ul>
FlexiPump® Scale + Weighing platform: Ø 17 x 5.4 cm + Adjustable dispensing arm (ref. 561 002)	<ul style="list-style-type: none"> <li>• Dimensions (W x D x H) : 40.8 x 39.1 x 43.4 cm</li> <li>• Net weight : 8.05 kg</li> <li>• Gross weight : 11.91 kg</li> </ul>
Boxing	<ul style="list-style-type: none"> <li>• Dimensions (W x D x H) : 50 x 40 x 40 cm</li> </ul>

## DELIVERED WITH

- 2 Watson Marlow™ peristaltic pump heads
- 1 weighing platform
- 1 3.2 mm dispensing assembly (nozzle + cap + GL45 bottle connector + filter + tubings + tube weight)
- 1 6.4 mm dispensing assembly (nozzle + cap + GL45 bottle connector + filter + tubings + tube weight)
- 1 power cord
- 1 user manual
- 1 USB cable
- 1 free pack of blender bags
- 1 certificate of conformity / warranty card

## ACCESSORIES

- Ref. 410 130 **Film for printer:** Thermal transfer film
- Ref. 410 150 **Printer:** Thermal printer (RS 232 and USB outputs). Delivered with 1 thermal transfer film + 1 power cord + 1 USB cable
- Ref. 413 002 **2 L bottles (GL45):** Set of 3 GL45 glass bottles (GL45), autoclavable
- Ref. 507 008 **Foot pedal:** for easy distribution (3.5 mm jack input)
- Ref. 511 000 **Booster kit:** Dispensing accelerator + 2 silicone tubings for pump (20 cm each) inner Ø 6.4 mm + 2 «Y»
- Ref. 513 001 **5 L bottle (GL45):** GL45 glass bottle (5 L), autoclavable
- Ref. 513 015 **Independent stand for broth bags:** Independent stand for 2 broth bags
- Ref. 521 012 **Labels for printer:** Set of 2 rolls of stickers for thermal printer - Label size: 70 x 45 mm
- Ref. 521 110 **Paper for printer:** Set of 2 rolls for thermal printer
- Ref. 561 001 **Handy gun:** Dispensing control by handy gun with electronic button to start distribution
- Ref. 561 002 **Adjustable dispensing arm:** To fill various containers
- Ref. 563 350 **BagOpen 3500 for peristaltic pumps (stainless steel):** Stainless steel bag opener for 3500 mL bags + Geckogrip. Compatible with FlexiPump Scale.

## TUBINGS

- Ref. 413 028 **Tube weights (Ø 3 mm):** Set of 5 tube weights (Ø 3 mm)
- Ref. 513 011 **Tubings for pump (Ø 4.8 mm):** Set of 6 Tygon™ tubings for pump part (20 cm) - Inner Ø 4.8 mm
- Ref. 513 020 **Trocar:** Stainless steel trocar + cap for broth bags
- Ref. 513 023 **0.2 µm PTFE filters (Ø 25 mm):** Set of 5 autoclavable PTFE filters (0.2 µm) for GL45 bottle
- Ref. 513 024 **Nozzles (tubings Ø 4.8 - 8 mm):** Set of 5 PEEK nozzles + caps for tubings from 4.8 to 8 mm inner diameter
- Ref. 513 039 **Tube weights (Ø 6 mm):** Set of 5 PTFE tube weights - Ø 6 mm
- Ref. 513 040 **Nozzles (tubings Ø 1.6 - 3.2 mm):** Set of 5 PEEK nozzles + caps for tubings from 1.6 to 3.2 mm inner diameter
- Ref. 513 048 **Cap (Ø 1.6 - 3.2 mm):** Set of 5 protections for nozzles (tubings Ø 1.6 - 3.2 mm) or trocar
- Ref. 513 052 **Tubings for pump Steriwater (Ø 6.4 mm):** Set of 2 Tygon™ tubings for pump part (50 cm) + 2 0.2 µm filters, inner Ø 6.4 mm
- Ref. 561 301 **Tubings for pump (Ø 1.6 mm):** Set of 6 Tygon™ tubings for pump part (20 cm). Inner Ø 1.6 mm
- Ref. 561 302 **Tubings for pump (Ø 3.2 mm):** Set of 6 Tygon™ tubings for pump part (20 cm). Inner Ø 3.2 mm
- Ref. 561 304 **Tubings for pump (Ø 6.4 mm):** Set of 6 Tygon™ tubings for pump part (20 cm). Inner Ø 6.4 mm
- Ref. 561 305 **Tubings for pump (Ø 8 mm):** Set of 6 Tygon™ tubings for pump part (20 cm). Inner Ø 8 mm
- Ref. 561 401 **Autoclavable GL45 stopper + 0.2 µm filter:** Autoclavable stopper for GL45 neck bottles + 0.2 µm filter
- Ref. 562 051 **Dispensing assembly + Y Steriwater (GL45 - Ø 6.4 mm):** Set of silicone tubings inner Ø 6.4 mm + GL45 plug + tube weight + strainer + nozzle + cap + "Y" + 2 0.2 µm filters - Compatible with FlexiPump® Pro / Scale
- Ref. 562 101 **Dispensing assembly + Y (GL45 - Ø 1.6 mm):** Set of silicone tubings, inner Ø 1.6 mm + GL45 screw cap + tube weight + nozzle + cap + filter + «Y»
- Ref. 562 102 **Dispensing assembly + Y (GL45 - Ø 3.2 mm):** Set of silicone tubings, inner Ø 3.2 mm + GL45 screw cap + tube weight + nozzle + cap + filter + «Y»
- Ref. 562 103 **Dispensing assembly + Y (GL45 - Ø 4.8 mm):** Set of silicone tubings, inner Ø 4.8 mm + GL45 screw cap + tube weight + nozzle + cap + filter + «Y»
- Ref. 562 104 **Dispensing assembly + Y (GL45 - Ø 6.4 mm):** Set of silicone tubings, inner Ø 6.4 mm + GL45 screw cap + tube weight + nozzle + cap + filter + «Y»
- Ref. 562 105 **Dispensing assembly + Y (GL45 - Ø 8 mm):** Set of silicone tubings, inner Ø 8 mm + GL45 screw cap + tube weight + nozzle + cap + filter + «Y»
- Ref. 562 201 **Tubings + Y (Ø 1.6 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner Ø 1.6 mm
- Ref. 562 202 **Tubings + Y (Ø 3.2 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner Ø 3.2 mm
- Ref. 562 203 **Tubings + Y (Ø 4.8 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner Ø 4.8 mm
- Ref. 562 204 **Tubings + Y (Ø 6.4 mm):** Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner Ø 6.4 mm

- Ref. 562 205 Tubings + Y (Ø 8 mm): Set of 5 dispensing tubings (silicone tubings + Tygon™ tubings + "Y" connectors) - inner Ø 8 mm
- Ref. 562 400 Y connectors (Ø 1.6 mm tubings): Set of 6 "Y" plastic connectors for Ø 1.6 mm tubings
- Ref. 562 401 Y connectors (Ø 6.4 - 8 mm tubings): Set of 6 "Y" plastic connectors for Ø 6.4 and 8 mm tubings
- Ref. 562 402 Y connectors (Ø 3.2 mm tubings): Set of 6 "Y" plastic connectors for Ø 3.2 mm tubings
- Ref. 562 403 Y connectors (Ø 4.8 mm tubings): Set of 6 "Y" plastic connectors for Ø 4.8 mm tubings

**PARIS**

Phone: +33 1 34 62 62 61  
[info@interscience.com](mailto:info@interscience.com)

**FRANKFURT**

Phone: +49 611 7238 7770  
[sales.germany@interscience.com](mailto:sales.germany@interscience.com)

**BOSTON**

Phone: +1 781 937 0007  
[sales.usa@intersciencelab.com](mailto:sales.usa@intersciencelab.com)

**SHANGHAI**

电话: +86 178 2123 6642  
[sales.china@interscience.cn](mailto:sales.china@interscience.cn)

**SINGAPORE**

Phone: +65 6977 7232  
[sales.asia@interscience.com](mailto:sales.asia@interscience.com)

**TOKYO**

Phone: +81 3 6712 9715  
[sales.japan@interscience.com](mailto:sales.japan@interscience.com)