

	<b>DiluFlow<sup>®</sup> Pro</b> <span style="float: right;">Ref. 502 205</span> Gravimetric dilutor (DiluFlow <sup>®</sup> Pro 5 kg, double pump)
	DiluFlow <sup>®</sup> is a gravimetric dilutor for the dilution of the sample before its microbiological analysis. All stainless steel with a new design, ultra-low profile for easy-use under laminar flow. USB port. Available with 1 or 2 pumps.  Compliant with ISO 7218, ISO 6887-1 and FDA BAM standards.

## TECHNICAL SPECIFICATIONS

- ▶ BagOpen<sup>®</sup> height < 30 cm
- ▶ Patented removable DripTray
- ▶ BagOpen<sup>®</sup> with GeckoGrip, patented
  
- ▶ Magnetic stand for BagOpen<sup>®</sup>, patented shape
- ▶ LightCode: color status LED
- ▶ Compatible with booster kit
- ▶ 304L stainless steel body
- ▶ Stainless casting electromechanical core
- ▶ Robotic arm
- ▶ Compatible with Jumbo kit
- ▶ Protection for tubing nozzle
  
- ▶ Resolution up to 200 g: 0.01 g
- ▶ Weighing range: 5000 g
- ▶ Weighing accuracy: 0 to 100 g: ± 0.05 g
- ▶ Weighing accuracy: 100 to 5000 g: ± 0.1 %
  
- ▶ Dilution factor: 1/2 to 1/99
- ▶ Dilution accuracy: >99% (with booster kit in standard or accurate mode)
- ▶ Dilution time for a 25 g sample diluted at 1/10: < 9 s (with booster kit in fast mode)
- ▶ Dilution time for a 375 g sample diluted at 1/10: < 80 s (with booster kit in fast mode)
- ▶ Dispensing time for 90 mL: < 7 s (with booster kit in fast mode)
- ▶ Dispensing time for 225 mL: < 10 s (with booster kit in fast mode)
- ▶ Max number of pumps: 2 integrated
- ▶ Dispensing/distribution mode: Fast - Standard - Accurate
- ▶ Traceability: Printer / Monitoring software (data export to: Excel<sup>™</sup> / Open Office<sup>™</sup> / CSV file / printer)
- ▶ Exported data: Sample weight / Total weight / Dilution factor / Dilution accuracy / Right or left pump + with monitoring software: Sample number / Name of operator / Date / Time
  
- ▶ Connection: RS232 output for printer / USB output for computer / Jack output for foot pedal
  
- ▶ Stainless steel
- ▶ Power: 100-240V~ 50-60Hz
- ▶ Weight: 15 kg
- ▶ Dimensions (w x d x h): 37 x 41.5 x 37.5 cm
  
- ▶ In compliance with ISO 7218, ISO 6887-1 and BAM (Bacteriological Analytical Manual) standards
  

---

- ▶ 1 year guarantee (after registration)
- ▶ Designed and made in France
- ▶ Manufactured under: ISO 9001 V2008, CE, WEEE 2002/96/EC, RoHS 2002/95/EC

---

## DELIVERED WITH

---

DiluFlow® Pro is delivered with 2 pumps, 1 DripTray 400, 1 protecting cap for nozzles, 1 dispensing assembly (GL45 - Ø 6,4 mm) per pump, USB cable, monitoring software, power cord, 1 BagOpen® 400 for dilutors, user's manual, quick user guide, certificate of conformity, guarantee, 10 GeckoGrip, free sample bags.

---

## ACCESSORIES

---

- ▶ **Ref. 410 150** Printer
  - ▶ **Ref. 521 110** Printer paper
  - ▶ **Ref. 521 012** Printer labels
  - ▶ **Ref. 410 130** Film for printer
  - ▶ **Ref. 507 008** Foot pedal
  - ▶ **Ref. 511 000** Booster kit
  - ▶ **Ref. 505 006** Jumbo Kit
  - ▶ **Ref. 513 001** 5L bottle (GL 45)
  - ▶ **Ref. 513 015** Independent stand for broth bags
  - ▶ **Ref. 505 010** Integrable stand for broth bags
  - ▶ **Ref. 513 020** Trocar
  - ▶ **Ref. 505 005** Adjustable distribution system
  - ▶ **Ref. 505 002** Weighing platform
  - ▶ **Ref. 505 003** Tongs platform
  - ▶ **Ref. 505 009** GeckoGrip
  - ▶ **Ref. 513 023** PTFE filters 0.2 µm (Ø 25 mm)
  - ▶ **Ref. 513 024** Set of 5 nozzles for tubings (inner Ø 4.8 to 8 mm)
  - ▶ **Ref. 513 040** Set of 5 nozzles for tubings (inner Ø 1.6 to 3.2 mm)
  - ▶ **Ref. 513 039** Set of 5 tube weights (Ø 6 mm)
  - ▶ **Ref. 513 005** Certified standard weight (500 g)
- 

## TUBINGS

---

- ▶ **Ref. 513 045** Dispensing assembly for single pump: inner Ø 3.2 mm (x1)
- ▶ **Ref. 513 043** Dispensing assembly for single pump: inner Ø 6.4 mm (x1)
- ▶ **Ref. 513 008** Dispensing assembly for booster kit: inner Ø 3.2 mm (x1)
- ▶ **Ref. 513 041** Dispensing assembly for booster kit: inner Ø 6.4 mm (x1)
- ▶ **Ref. 561 202** Silicone tubings for single pump: inner Ø 3.2 mm (x5)
- ▶ **Ref. 513 044** Silicone tubings for single pump: inner Ø 6.4 mm (x5)
- ▶ **Ref. 513 009** Silicone tubings for booster kit: inner Ø 3.2 mm (x5)
- ▶ **Ref. 513 042** Silicone tubings for booster kit: inner Ø 6.4 mm (x5)
- ▶ **Ref. 561 302** Silicone tubings for pump head: inner Ø 3.2 mm (x6)
- ▶ **Ref. 561 304** Silicone tubings for pump head: inner Ø 6.4 mm (x6)