

easySpiral® Automatic plater Ref 412 000



Standards :



Manufactured under :



Products made for INTERSCIENCE by Interlab, an ISO 9001 certified company

easySpiral® is an automatic plater for Petri dishes plating a liquid sample from 300 to 1.3x10⁵ CFU/mL on one Petri dish without prior dilution.

TECHNICAL SPECIFICATIONS

- Plating modes: exponential and **circle**
- Petri dish diameter: 90 mm
- Preset dispensed volumes: 50 or 100 µL
- Counting range: from 300 to 1.3x10⁵ CFU/mL
- Exponential mode: 4 dilutions logs on Ø 90 mm Petri dish
- Volumes accuracy: ± 0,5 % (in normal mode)
- **Syringe capacity: 1000 µL**
- **Plating time: 8 seconds**
- **Plating cycle: 1 disinfection + 1 sample intake + 1 plating: 25 seconds**
- **Plating capacity with the same sample: up to 20 Petri dishes (50 µL)**
- **Multi-use, autoclavable stylus**
- **Cleaning and disinfection of the stylus by "Overflow" technology. Pression: up to 8 bars (Patented)**
- Automatic disinfection program
- Approved disinfectants: bleach 1 to 2 % active chlorine or ethanol at 70 %
- **Security detection in case of lack of disinfection liquid**
- **Disinfectant autonomy (in normal mode): 1000 cycles (2 L bottles)**
- **Distilled water autonomy: 600 cycles (2 L bottles)**
- **All stainless steel**
- Controlled by microprocessor
- **Fast rotating arm (Patented)**
- Test key for checking plating volumes (volumetric volumes)
- Sample intake possible in Eppendorf™ 0.5/1.5/ 2 mL beaker or Dilucup™

- Voltage and frequency: 100-240V~ 50-60Hz
- Fuses: 1.6A T 240V 5x20 mm
- Max power: 45 W

- Dimensions (w x d x h): 40 x 41.5 x 29 cm, weight: 16.4 kg
- Box (w x d x h): 60 x 50 x 55 cm, weight: 24.6 kg

- Warranty: 1 year

- In compliance with standards ISO 7218, ISO 4833-2, FDA BAM (Bacteriological Analytical Manual), AOAC 977.27
- Manufactured under CE, ROHS, WEEE - Products made for INTERSCIENCE by Interlab, an ISO 9001 certified company
- Designed and Made in France

DELIVERED WITH

- 1 plating ring for Ø 90 mm Petri dishes (by default on the unit)
- 1 box with:
 - 1 blue dye for testing (Ref 415 530)
 - 1 syringe with silicone tubing
 - 1 **Spiral**® counting grid for Ø 90 mm Petri dishes (Ref 413 014)
 - 1 container stand for testing
 - 1 set of 2 filters (Ref 413 009)
- 1000 **Spiral**® DB50 beakers (Ref 415 100)
- 1 **EnzyClear**® detergent (Ref 413 029)
- 4 sets of GL45 connectors (Ref 413 003)
- 1 sets of GL45 connectors double port (Ref 414 004)
- 1 stylus (Ref 414 001)
- 1 power cable
- 1 user's manual
- 1 **EnzyClear**® quick user guide

OPTIONS / ACCESSORIES

- Ref 413 001 **Housing protection for platers:** Transparent housing for working under laminar flow
- Ref 413 002 **2 L Bottle (GL45):** 2 L GL45 glass bottle
- Ref 413 003 **Connection kit for GL45 bottles:** Autoclavable connection set for GL45 bottles
- Ref 413 004 **1 mL syringe:** Syringe (1000 µL capacity)
- Ref 413 005 **Micro-pump:** Internal micro-pump
- Ref 413 006 **Tubings:** Silicone tubings with filter for cleaning pump
- Ref 413 014 **Spiral**® (90 mm) counting grid: Counting grid for Ø 90 mm Petri dishes
- Ref 413 016 **Support for Eppendorf™ 0.5 mL:** Support for 0.5 mL Eppendorf™ sample intake
- Ref 413 017 **Support for Eppendorf™ 1.5 and 2 mL:** Support for 1.5 and 2 mL Eppendorf™ sample intake
- Ref 413 018 **Support for Dilucup™:** Support sample intake for Dilucup™
- Ref 413 026 **Circle counting grid (90 mm):** Circle mode counting grid for Ø 90 mm Petri dishes
- Ref 413 029 **EnzyClear®: Spiral**® plater recommended detergent for cleaning and pre-disinfection
- Ref 414 001 **Stylus (1 mL):** 1 mL stylus
- Ref 414 003 **Maintenance kit for platers (1 mL):** Maintenance kit (1 stylus + 1 syringe + 1 silicone tubing, 1 grease tube, 8 pump filters, 2 quick connectors)
- Ref 414 004 **Double connection kit for GL45 bottles:** Double connection kit for GL45 bottle to be used on the same bottle
- Ref 415 100 **DB50 beakers:** 1000 beakers for **Spiral**® plater (5 mL)
- Ref 415 530 **Blue dye for plater:** Blue dye for **Spiral**® tests (125 mL)
- Ref 513 023 **0.2 µm PTFE filters (Ø 25 mm):** Set of 5 autoclavables filters (0.2 µm)