

	Scan[®] 1200 High Resolution inhibition zone reader	Ref. 437 000
	<p>Scan[®] 1200 is an inhibition zone reader for antimicrobial susceptibility testing. It enables checking the susceptibility of bacteria to antibiotics and offers quick, traceable and complete results to validate a medical choice.</p> <p>In compliance with CFR 21 part 11, EUCAST, CA-SFM, ISO 7218, ISO 4887-2</p>	

TECHNICAL SPECIFICATIONS

- All stainless steel body
- Color HD CCD camera
- HD japanese lens
- Digital zoom x28 (enabling to read the letters on the disks)
- Resolution : 1.2 mega-pixels
- Counting time: 1000 colonies per second
- Minimum size of colony: 0.05 mm
- Lighting system: long-life white LEDs / Dark Field
- Lighting system: automatic 6 combinations, top and/or bottom light, white or black background

- Counting: automatic with manual control
- Results / data export: Scan[®] recountable file, PDF report, jpeg, png, bmp, Excel[™]
- LIMS connection
- USB connection
- Counting on Petri dishes (55 - 90 mm)
- Spiral[®] plating
- Color detection: 7 colors on the same dish
- Counting on chromogenic medium
- Inhibition zone measurement
- Counting on PetriFilm[™]
- Counting on RIDA[™] Count
- Counting on Compact Dry[™]
- Counting on filtration membrane

- Automatic separation of confluent colonies
- Automatic elimination of counting grids
- Polygonal exclusion areas

- Automatic detection of paper disks (all brands simultaneously), wells, peni-cylinders (steel, plastic), customizable, add/subtract manually
- Inhibition zone reader : automatic with possible manual check-up
- Number of antibiotic paper disks: up to 8 antibiotics on a 90 mm Petri dish
- Reading time: 8 inhibition zone reading in 1 - 3 seconds

- Interpretation system : CA-SFM Human health / EUCAST / CA-SFM Veterinary / customizable list
- Security of data: saving of all changes in compliance with CFR 21 recommendations /
- Results / Traceability : image / sample number & antibiotic name / bacteria name / read diameter / result with category SIR by color code (Sensitive / Intermediate / Resistant) / critical diameter mini and maxi /comments / date / time

- Software available in french, english, spanish, japanese, chinese, russian

- Power : 100-240V~ / 50-60Hz
- Dimensions : (W x D x H) : 28 x 27 x 38 cm, weight : 9.3 kg
- Box : (W x D x H) : 42 x 42 x 56 cm, weight : 13 kg
- Guarantee (after registration): 3 year
- Software update (after registration): 3 year
- In compliance with CFR 21 part 11, EUCAST, CA-SFM, ISO 7218, ISO 4887-2
- Designed and made in France
- Manufactured under: ISO 9001 V2008, CE, WEEE 2002/96/EC, RoHS 2002/95/EC standards

MINIMUM COMPUTER REQUIREMENTS

- Processor : Intel Core (recommended) or AMD Phenom or superior
- Operating system : Windows 7 SP1 or Windows 8 or superior
- Frequency : 2,4 Ghz or superior
- RAM : 3 Go
- Features: CD ROM reader, USB port
- Screen resolution: 1280 x 1024 pixels

DELIVERED WITH

- Scan® software on CD-ROM
- Connection cables
- 3 control dishes
- User's manual, IQ/OQ/PQ guidelines
- Quick user guide

OPTIONS/ACCESSORIES

- Ref. 436 001 DataLink™, traceability system
- Ref. 436 001 RIDA COUNT™ / Sanita-kun™adaptors
- Ref. 436 002 PetriFilm™ adaptor
- Ref. 436 004 Compact Dry™ adaptor
- Ref. 436 005 55 mm Petri dish adaptor
- Ref. 436 100 Desk computer (Dell with Windows 7 or Windows 8 with programm installed)
- Ref. 522 000 Bar-code reader